



PRODUCT DATA SHEET

MEDIUM GRADE

Benefits:

- Biodegradable
- Non-Carcinogenic
- Non-Leaching
- Non-evaporative
- Non-conductive to 70kv
- Penetrates into surface rust
- Penetrates into grooves and joints
- Resists acids and salts
- Hermetically seals off surfaces
- Stays On
- Won't break down rubber and wiring
- Safe to use in food areas where NSF International food rating is required H1, H2, R2 or NZFSA C12.

Sizes:

- 300grm aerosol
- 1 Litre
- 4 Litre
- 20 Litre
- 200 Litre

Uses:

- Chassis protection on Quad Bikes
- General workshop lubricant and penetrant
- Spare parts in storage
- Electrical connections
- Rust preventative and lubricant on boat, motors, engine covers, and trailers.



- Freeing up tools, hinges, fittings, locks etc

Contents

- Lanolin, blended with non-regulated, paraffin carriers to assist with penetration and ease of application

Physical Properties

- State; Liquid-light brown colour
- Insoluble in water
- Relative vapour density (air=1): 5.3
- Lower explosive limit (%): 1.0
- Upper Explosive limit (%); 6.0
- Auto-ignition Temp (°C): 227
- Boiling Range (°C): 110-200
- Specific Gravity (water=1): 0.81-0.83 @24 °C
- Vapour Pressure (kPa): 0.4 @ 38°C
- Evaporation Rate: 0.05 (BuAc=1)
- Flash Point (°C): 66
- Viscosity (B-Viscos): 15.0
- Non conductive point: 70Kv

Contact Details

Prolan NZ Ltd

Phone: +64 7 5480823

Email: murray@prolan.co.nz

Fax: +64 75480823

Web: www.prolan.co.nz

High Performance Lanolin Lubricant