



General Engineering

Prolan Medium Grade

SIZES : 300gm aerosol, 1 litre, 4 litre and 20 litre.

PROLAN LANOLIN LUBRICANTS

Prolan is an all-purpose natural lanolin lubricant and corrosion inhibitor. Its unique properties surpass other petrochemical products in performance, reliability, longevity, protection, safety and asset maintenance. Medium grade liquid lanolin will preserve, lubricate, and protect your assets long term.

RECOMMENDED USES

- Excellent rust protectant for storage of parts to stop surface rust.
- Use as general workshop lubricant to lubricate or free up frozen joints from rust.
- Spray around electrical connections to prevent moisture penetration and prevent corrosion and electrolysis.
- Non-conductive to 70Kv won't break down rubber and wiring.
- Moisture barrier.
- Cutting or tapping lubricant.
- Safe to use in food areas where NSF International food rating is required H1, H2, R2 or NZFSA C12.
- Welding anti-splatter.
- Wire rope lubricant.



FEATURES

- Long lasting protection saving time on multiple reapplication
- Won't break down rubber and wiring.
- Stops corrosion by preventing air and moisture attack.
- Most surfaces can be water-blasted, Prolan will not be affected.
- When used in the workshop for a general lubricant it eliminates the need for multiple products.
- Safe to use, environmentally friendly and biodegradable.

APPLICATION

- Shake can well and spray onto the surface or into the joints.
- If left overnight or longer it will attract less dust and dirt leaving a cleaner finish.
- When using as joint lubricant, have a rag handy to wipe off the excess, as whatever is left behind will leave the joint lubricated for long period.