



## General Engineering

### Prolan Grease Anti Seize

SIZES : 500ml, 4 litre and 20 litre

### PROLAN LANOLIN LUBRICANTS

Prolan is an all-purpose natural lanolin lubricant and corrosion inhibitor. Its unique properties surpass other petrochemical products in performance, reliability, longevity, protection, safety and asset maintenance. Prolan grease anti-seize will preserve, lubricate, and protect your assets long term.

### RECOMMENDED USES

- Extremely good anti-seize to use in assembly/disassembly of components. Not suitable for high temp applications.
- Extremely good anti seize for prevention of galling on stainless steel threads.
- Added electrolysis barrier between dissimilar metals.
- Non-conductive to 70kv.
- Smear around all electrical connections to prevent moisture corrosion.
- Assembly of components that have to be removed or opened up for regular maintenance.
- Excellent in slow moving pins and bushes as water is unable to wash it out.



### FEATURES

- Long lasting protection saving time on multiple reapplication
- Will stay in the joint or threads for long periods and allow easy removal of components anytime in the future.
- Can't be washed out of the joint by high pressure water blasting or salt water.
- Won't break down rubber and wiring.
- Seals off the surfaces from air and moisture and prevents corrosion.
- Safe to use, environmentally friendly and biodegradable.

### APPLICATION

- Apply to thread or flat surface using finger, rag or by dipping the component into the tub.



## General Engineering

### Prolan Medium Grade

SIZES : 300gms aerosol, 1 litre, 4 litre and 20 litre.

### PROLAN LANOLIN LUBRICANTS

Prolan is an all-purpose natural lanolin lubricant and corrosion inhibitor. Its unique properties surpass other petrochemical products in performance, reliability, longevity, protection, safety and asset maintenance. Medium grade liquid lanolin will preserve, lubricate, and protect your assets long term.

### RECOMMENDED USES

- Excellent rust protectant for storage of parts to stop surface rust.
- Use as general workshop lubricant to lubricate or free up frozen joints from rust.
- Spray around electrical connections to prevent moisture penetration and prevent corrosion and electrolysis.
- Non-conductive to 70Kv won't break down rubber and wiring.
- Moisture barrier.
- Cutting or tapping lubricant.
- Safe to use in food areas where NSF International food rating is required H1, H2, R2 or NZFSA C12.
- Welding anti-splatter.
- Wire rope lubricant.



### FEATURES

- Long lasting protection saving time on multiple reapplication
- Won't break down rubber and wiring.
- Stops corrosion by preventing air and moisture attack.
- Most surfaces can be water-blasted, Prolan will not be affected.
- When used in the workshop for a general lubricant it eliminates the need for multiple products.
- Safe to use, environmentally friendly and biodegradable.

### APPLICATION

- Shake can well and spray onto the surface or into the joints.
- If left overnight or longer it will attract less dust and dirt leaving a cleaner finish.
- When using as joint lubricant, have a rag handy to wipe off the excess, as whatever is left behind will leave the joint lubricated for long period.