



Long Term Rust Preventative

Prolan Enduro Heavy Grade

SIZES : 1 litre, 4 litre and 20 litre.

PROLAN LANOLIN LUBRICANTS

Prolan is an all-purpose natural lanolin lubricant and corrosion inhibitor. Its unique properties surpass other petrochemical products in performance, reliability, longevity, protection, safety and asset maintenance. Enduro Heavy grade liquid lanolin will preserve, lubricate, and protect your assets long term by placing a waxy film on the surface.

RECOMMENDED USES

- As a rust preventative film on vehicle chassis or bike frames in highly corrosive environments.
- As a rust preventative for equipment being shipped overseas.
- Use as a protectant for equipment being stored for long periods.
- Under the floor of boat hulls to prevent electrolysis and salt water corrosion.
- Spray around electrical connections to prevent moisture penetration and electrolysis.
- Non-conductive to 70Kv won't break down rubber and wiring.



- Moisture barrier.
- Safe to use in food areas where NSF International food rating is required H1, H2, R2 or NZFSA C12.
- Wire rope lubricant.

FEATURES

- Shiny finish with less tackiness than other lanolin products and therefore won't attract the dust.
- Surfaces can be cold water-blasted, Prolan will not be affected.
- Stops corrosion by preventing air and moisture attack.
- Long lasting protection saving time on multiple reapplication
- Won't break down rubber and wiring.
- Safe to use, environmentally friendly and biodegradable.

APPLICATION

- Shake can well and spray onto the surface or into the joints.
- If left for as long as possible it will attract less dust and dirt leaving a cleaner finish.



Medium Term Rust Preventative

Prolan Enduro Medium Grade

SIZES : 1 litre, 4 litre and 20 litre.

PROLAN LANOLIN LUBRICANTS

Prolan is an all-purpose natural lanolin lubricant and corrosion inhibitor. Its unique properties surpass other petrochemical products in performance, reliability, longevity, protection, safety and asset maintenance. Enduro Medium grade liquid lanolin will preserve, lubricate, and protect your assets long term by placing a waxy film on the surface.

RECOMMENDED USES

- As a rust preventative film on vehicle chassis or bike frames in applications that can be recoated in 12-24 month intervals.
- As a rust preventative for equipment being shipped overseas.
- On equipment in dirty environments where you don't want the dust sticking to the surface
- On marine outboard and inboard engines.
- Spray around electrical connections to prevent moisture penetration and electrolysis.
- Non-conductive to 70Kv won't break down rubber and wiring.



- Moisture barrier.
- Safe to use in food areas where NSF International food rating is required H1, H2, R2 or NZFSA C12.
- Wire rope lubricant.

FEATURES

- Shiny finish with minimal tackiness compared to other lanolin products and therefore won't attract the dust.
- Surfaces can be cold water-blasted, Prolan will not be affected.
- Stops corrosion by preventing air and moisture attack.
- Won't break down rubber and wiring.
- Safe to use, environmentally friendly and biodegradable.

APPLICATION

- Shake can well and spray onto the surface or into the joints.
- If left for as long overnight dry off it will form an outer skin that will not attract dust and dirt leaving a cleaner finish.