

NZ Quad bike riders fight the war against Rust

Quad bikes are an essential part of the New Zealand dairy farmer and recreational riders world. The corrosive nature of the cow manure on farms and salt from beaches causes the framework of the quad bike to rust out. Some bikes are treated with a diesel and oil mixture, however this evaporates off and breaks down in approximately 3 months. Most frames rust through on the front steering wishbone where the muck has built up over the top, and the owner is therefore unaware what is happening underneath or the safety issues about to present themselves. When the wishbone finally gives way all steering is lost and the bike is off over a bank or into a drain.

Solution

- Spraying 'Prolan Enduro Medium grade Spray' forms a barrier from the cow manure or salt and stops the air and moisture attacking the surface and causing corrosion.
- This coat will last 9-12 months on the average farm bike depending upon the situation. Beach bikes could be up to 2 yrs depending the situation.
- Medium grade is better than the heavy grade for beach applications as the thinner coating stops sand build up.

The advantage of the 'Prolan Medium grade Enduro Liquid' is:

- It's affinity for sticking to the steel which will stop the cold water blasting from washing it off. The 'Prolan protective Lubricant' always stays soft and moves with the frame preventing the coat from cracking.
- It is also a clean easy to use biodegradable product that will not affect the environment.

Results

- Treatment is only required every 9-12 months and the bike can be washed in between coats of Prolan.
- As you can see in the photo above, the frame on this bike is still in good condition after 14000kms.

Testimonial

Dave who has a quad bike on the farm tells his story. Please hold down the ctrl key and click on the attached link to see his video. <http://www.youtube.com/watch?v=u1b9r5yfR6k>





PROLAN HEAVY GRADE ENDURO PERFORMS EXCELLENT AS A CHASSIS CORROSION INHIBITOR.

Prolan Enduro Heavy Grade Liquid Lanolin will preserve, lubricate and protect your assets long term by placing a waxy film on the surface. Once applied Prolan will last on for a long period of time – is easy to apply and clean to use.



FEATURES:

- Shiny finish with less tackiness than other lanolin products and therefore won't attract the dust.
- Surfaces can be cold water-blasted, Prolan will not be affected.
- Stops corrosion by preventing air and moisture attack.
- Long lasting protection saving time on multiple reapplication
- Won't break down rubber and wiring.
- Safe to use, environmentally friendly and biodegradable.

APPLICATION:

- Shake Prolan well and spray onto the surface or into the joints, panels. Using a trigger pack spray, garden sprayer or airless spray gun e.g. airboy undersealer gun as seen in pictures below.
- Once coated leave to dry for as long as possible, overnight as a minimum preferably 3-4 days- it will attract less dust and dirt leaving a cleaner finish.

REMOVAL:

- Prolan can be removed by hot water steam cleaning.
- Prolan degreaser/cleaner once applied and left for ten minutes will remove Prolan Enduro coatings with a cold water-blaster. Returning your asset back to its original condition – with NO RUST.

